



SHELBER STONE SEALER ECO PLUS S1337

WATER-BASED PENETRATING SEALER FOR NATURAL STONES

DESCRIPTION:

The product is a water-based penetrating sealer to be used as pre-grouting sealer for natural stones. In this case the application should be done before the installation of the stone tiles. The products can be used even on already installed surfaces, to provide protection from water absorption and humidity-related stains.

The product does not create superficial film, does not alter the original breathability of the treated surface and does not alter the original look.

ADVANTAGES:

- Water-based
- Natural look
- Does not form a film

WHERE TO APPLY:

For **outdoor** or **indoor** application. Recommended for use on natural stones

COVERAGE: 10-15 sq.mt/lt.

CAN BE APPLIED WITH:



USE:

Test on a small area before proceeding, so to ensure product suitability and final result.

Apply the product to a dust free, dry or slightly damp material, by immersion, with a sprayer, a brush or with a lamb's skin wool. After 5 to 10 minutes (just a few seconds in the factory plant) even out the product left on the surface with a lambswool applicator, a brush or a roller, spreading it until all of the residues are removed. After treatment, wait 24 hours at least before setting or grouting.

If the product has not been completely removed, especially after treatment at stonemasonries, it tends to make very stubborn dry residues on the surface. Such residues can be removed after setting by washing with a single disc machine and white pad and some detergent water.



Technical data sheet

Revision: 24/03/2017

Version: 23.0

TECHNICAL DATA:

Aspect	: Liquid
Color	: Transparent
Odour	: Odourless
Specific gravity (20°C)	: 1010 ± 10 g/lt.
pH	: 11.0 ± 0.4

STORAGE:	Store containers tightly closed, in a cool and dry place.
SHELF LIFE:	36 months in the original sealed packaging, stored in a cool and dry place.
PACKAGING:	1 lt. bottles (12 per carton) - 4 lt. cans (4 per carton) - 25 lt. cans

SAFETY



H 315 : Causes skin irritation
H 319 : Causes serious eye irritation.
P264: Wash ... thoroughly after handling.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302 + P352: IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313: If skin irritation occurs: Get medical advice/attention.
P362: Take off contaminated clothing and wash before reuse..

IMPORTANT

Technical information and suggestions are based on our experiences. We guarantee a high quality product. However, we are not responsible for results obtained when the product is used under conditions beyond our control. The characteristics of the various materials may differ in structure, absorption and mineral composition: it is always advisable to do a preliminary test on a small surface before final application.

LIMITATIONS OF LIABILITY

Please note that the information provided is a guideline and do not represent a formal guarantee for the end user. In particular, it is noted that the responsibility for B-Chem S.r.l. in case of problems caused by defective products, once the defect is verified, it is limited to the purchase price of the product. B-Chem S.r.l. assumes no liability for damage caused by improper use of the product remained outside our control.

Specifications given by:

B-CHEM S.r.l.
VIA Enzo Ferrari, 68 – Industrial Area “A”
62012 CIVITANOVA MARCHE (MC) - ITALY
Tel. + 39 0733 801444, Fax + 39 0733 801062
info@b-chem.net - www.b-chem.net

ISO 9001 CERTIFIED ORGANISATION



United Registrar of Systems Cert No. 14199